

CONTROL YOUR FUTURE

**FumeVac**® By IVEC Systems, LLC



Fume Extraction Source Capture Suction is OFF



Fume Extraction Source Capture Suction is ON

GENERAL SPECIFICATIONS

**FumeVac IVFE-120 and IVFE-225** Portable fume extractors are the most efficient and versatile solution for fume and dust source capture when central vacuum systems cannot be used or are too expensive.

IVFE portable models are specifically designed for manufacturing processes such as **welding** and **grinding**. They are **easily transportable and offer minimal cost of ownership**.

Each model is available with :

- 14" (120 sq. ft.) or 26" (225 sq. ft.) High Efficiency Filter
- Panel Mount Breaker
- IVFE 120 has NEMA 5-20P Plug
- IVFE 225 has NEMA L14-20P Plug
- Manometer
- On/Off switch
- 2 inch inlet

Model	Diameter (in)	Height (in)	Weight (lbs)	Voltage (V)	Power (kW)	Frequency (Hz)	Max Flow (CFM)	Max Vacuum ("H2O)	Filter Surface (sq ft)	Filter Eff @ 0.5 micron (%)	Noise Level @ 5' (dB)
IVFE-120-1	17	31	55	120	1.67	50/60	137.5	140	120	99.9	76
IVFE-225-1	17	43	65	120	1.67	50/60	137.5	140	225	99.9"	76
IVFE-120-2	17	31	60	240	3.34	50/60	275	140	120	99.9	78
IVFE-225-2	17	43	70	240	3.34	50/60	275	140	225	99.9	78

Options Available: FV-HEPA-SC: HEPA filter and adapter ● FV-DDSG: Welding Gas Signal Remote Starter

